

(12) UK Patent Application (19) GB (11) 2 381 048 (13) A

(43) Date of Printing by UK Office 23.04.2003

(21) Application No 0229414.8

(22) Date of Filing 20.06.2001

(30) Priority Data

(31) 0015207

(32) 21.06.2000

(33) GB

(86) International Application Data

PCT/GB2001/002753 En 20.06.2001

(67) International Publication Data

WO2002/001036 En 03.01.2002

(71) Applicant(s)

Neylor-Weir Limited
(Incorporated in the United Kingdom)
Bellevue Road, Clackmannan, Fife,
FK10 1NR, United Kingdom

(72) Inventor(s)

Andrew Downie
Guido Ernesto Pezzani
Edward Docherty Scott

(51) INT CL⁷

E21B 4/02, F01D 5/02 9/04 11/18 15/00, F03B 3/04
3/12 3/16 13/02

(52) UK CL (Edition V)

F1V VB VCF VCO V106 V108 V111 V202 V204 V214
V308 V310
F1T TA TC T102 T109 T119 T129 T131 T149 T202 T302
T311
U1S S1248 S1987

(56) Documents Cited by ISA

US 4850818 A US 4832573 A
US 4114702 A

(58) Field of Search by ISA

INT CL⁷ E21B, F01D, F03B, F04D, F16D
Other:


(74) Agent and/or Address for Service

Cruikshank & Fairweather
19 Royal Exchange Square, GLASGOW,
G1 3AE, United Kingdom

(54) Abstract Title

Drilling turbine

(57) A turbine (10) is disclosed which includes a turbine blade housing (14) having an inner facing portion (22) of a first material having a first coefficient of expansion, and a turbine blade body (16) having an outer facing portion (24) of a second coefficient of expansion greater than said first coefficient. In a preferred embodiment, the blade housing (14) comprises a number of steel shroud rings (26) and the turbine blade body (16) comprises a number of stators (32) and rotors (34) of a thermoplastic material. An interference fit between stator blades (38) and the shroud rings (26) is enhanced in use due to the difference in thermal and/or hydrophilic coefficients of expansion of the first and second materials.



GB 2 381 048 A